Installation Manual



36"



48"



60"

Shower Base

Please record the model number found on the front panel of the box.

Model Number: _____

Retain these instructions for future use.

P/N 27793 09/13

PARTS INCLUDED



	A	B	C	D	E
36" Base	17" (43.4 cm)	35-7/8" (91.1 cm)	34-3/4" (88.2 cm)	4.5" (11.3 cm)	18" (45.7 cm)
48" Base	16" (40.9 cm)	47-7/8" (121.6 cm)	32-3/4" (83.1 cm)	4.5" (11.3 cm)	24" (61.0 cm)
60" Base	15" (38.3 cm)	59-7/8" (152.1 cm)	30-3/4" (78.1 cm)	4.5" (11.3 cm)	8-1/2" (21.4 cm)*

* 60" base available with right or left side plumbing.

REQUIREMENTS FOR SUCCESSFUL INSTALLATION

⚠ **CAUTION: DO NOT** use drywall screws to secure flanges to wall studs. Product damage will occur and will void the warranty.

- **Read complete instructions before beginning installation.**
- **These instructions include suggestions for rough construction and plumbing installation that we believe to be reliable. Local building codes vary and could supersede those suggestions. If you are not confident in your ability to perform these tasks, contract out those tasks you need help with or use a professional installer.**
- **Confirm that your model will fit in intended location and plumbing fixtures are located where required before beginning installation.**
- **Walls and sub-floor must be solid, plumb, and square.**
- **Use drop cloth to protect shower base from damage during installation.**
- **Do not install in areas where temperature may drop below 32°F (0°C).**
- **Allow product to reach room temperature for 30 minutes before installation.**
- **Two people recommended to install this product.**

TOOLS AND MATERIALS REQUIRED

Safety glasses


Utility knife

Pencil


Tape measure


Shims


Drop cloth


Square


Level


Caulk gun


Adhesive (2 tubes)


Sealant (2 tubes)

Drill

1-1/4" screws (zinc or stainless; panhead or roundhead)


2-1/2" construction screws

Hole saw (sized to accommodate plumbing fixtures)

Extension bit holder (recommended)

#2 Phillips bit (for use with extension bit holder)


Drill bit 3/16" (5 mm)

- 2” x 4” lumber for additional wall studs
- Lumber for bracing
- Rags or padding to protect product during bracing

TIP: You may want to install insulation.

ROUGHING-IN

36"



48"



60"





- Rough plumbing must be installed before panel installation.
- Minimum stud pocket sizes are shown above.

* 60" base available with right or left side plumbing. Right side plumbing rough-in shown.

****IMPORTANT!** If installing wall set, refer to wall set installation instructions for specific lumber sizes and placement. Additional studs will be required and need to be installed at this point.

- For masonry construction, floor and walls must be framed to accommodate plumbing and installation.

BASE INSTALLATION

Important Instructions For Proper Installation



⚠ CAUTION: Drill chuck can damage base. Drill holes from back side of side base.

TIP: If installation surface is not level, use leveling compound or mortar bed for proper installation.

1. Symbols and Descriptions

A APPLY ADHESIVE where indicated.

S APPLY SEALANT where indicated.

⚠ CAUTION: A situation which, if not avoided, could result in property damage or other undesirable conditions. Product damage will occur and will void the warranty.

IMPORTANT! Instructions which, if not followed, could result in property damage. Product damage may occur and will void the warranty.

2. Verify Base Fit



Position base and verify that it is straight and square.

⚠ CAUTION: Entire bottom support must be in contact with a flat level surface.

TIP: If installation surface is not level, use leveling compound or mortar bed for proper installation.

3. Prepare Base



- Trace outline of drain and base.

4. Attach Drain



- Attach drain following manufactures's instructions.

⚠ CAUTION: Plumber's putty will degrade base material. Do not use plumber's putty to seal between drain and base. Use latex/acrylic sealant or a gasket.

5. Drill Holes in Flange



- Drill 3/16" holes at all stud locations on top flanges.

⚠ CAUTION: Drill 3/16" clearance holes into flanges only. Do not drill 3/16" holes directly into studs. Drill chuck can damage base. Use an extended bit holder to reduce risk of drill chuck hitting base.

6. Install Drain Pipe



- Ensure that the waste pipe is properly located to align with the drain assembly (not included).
- The opening should be 5" in diameter. The drain pipe should extend 1-3/4" above the subfloor.

7. Optional



- If the subfloor is not flat and level, it is recommended to put down a mortar bed where the base will be positioned.

8. Apply Adhesive



A APPLY ADHESIVE on floor and spread using the notched side of the trowel, starting within pencil line.

9. Final Base Placement



- Place base on adhesive covered floor and recheck level. Adjust if necessary.

10. Insert Cardboard



- Insert cardboard or other material into the base to protect surface.

> **⚠ CAUTION:** Do not remove until all work has ceased in room.

11. Secure Base



- Secure flanges to wall studs with 1-1/4" screws.

⚠ CAUTION: Use panhead or roundhead screws. Do not overtighten screws, this can cause base to crack.

IMPORTANT! Gaps between flanges and studs must be less than 1/8". Insert shims to fill gaps.

12. Apply Sealant



⚠ CAUTION: After installing finished walls, remember to apply sealant to all outer edges.

Ⓢ APPLY SEALANT to all seams.

IMPORTANT! Follow manufacturer's instructions for sealant dry time before use.

13. Proceed to Wall Set



- If installing our matching wall set, proceed with "Wall Set Installation" instructions.

CUSTOMER SERVICE

For product and installation questions, DO NOT return to the store. For additional help contact customer service:

Visit www.deltabathing.com, e-mail bathingsystems@deltafaucet.com, or call ☎ 1-877-430-5315.

CARE AND CLEANING

For regular cleaning use ONLY mild detergents or warm, soapy water. Use ONLY non-abrasive cloth or sponge. Always rinse surfaces after cleaning.

Before cleaning this product with cleaning products, test a small, inconspicuous area.

⚠ **CAUTION:** The manufacturer does not recommend the use of cleaning products that contain any of the following chemicals. Use of products containing these chemicals can cause the product to crack or discolor and will void the warranty.

- Naphtha
- Amyl Acetate
- Hydrogen Peroxide Solution (common household peroxide)
- Toluene
- Ethyl Acetate
- Lye (common in drain cleaner)
- Acetone

LIMITED WARRANTY

All parts and finishes of the Delta® shower unit are warranted to the original consumer purchaser to be free from defects in material and workmanship for the time periods listed below. Delta recommends using a professional plumber for all installation and repair. Delta will replace, FREE OF CHARGE, during the warranty period, any part or finish that proves defective in material and/or workmanship under normal installation, use and service for the time period listed below:

• Non-residential or commercial application - 3 years • Residential applications - 10 years

This warranty is extensive in that it covers replacement of all defective parts and even finish, but these are the only two things that are covered. LABOR CHARGES AND/OR DAMAGE INCURRED IN INSTALLATION, REPAIR, OR REPLACEMENT, AS WELL AS ANY OTHER KIND OF LOSS OR DAMAGE ARE EXCLUDED. Proof of purchase (original sales receipt) from the original consumer purchaser must be made available to Delta for all warranty claims. THIS IS THE EXCLUSIVE WARRANTY BY DELTA, WHICH DOES NOT MAKE ANY OTHER WARRANTY OF ANY KIND, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. Any damages to this product as a result of misuse, abuse, or neglect WILL VOID THE WARRANTY.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. It applies only to Delta® Shower Units installed in the United States of America, Canada and Mexico.

If you have any questions regarding technical support, installation or concerns regarding our warranty plan, please view our Warranty Frequently Asked Questions at www.deltafaucet.com/bathingsystems, email us at bathingsystems@deltafaucet.com, or call 1-877-430-5315.

DISCLAIMER: IMPLIED WARRANTIES, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE, ARE LIMITED TO THE DURATION OF THIS WARRANTY. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. TO THE EXTENT PERMITTED BY LAW, THIS WARRANTY DOES NOT COVER SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (SUCH AS LABOR EXPENSES) WHETHER ARISING OUT OF BREACH OF WARRANTY, BREACH OF CONTRACT, TORT, OR OTHERWISE. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation of exclusion may not apply to you. This warranty gives you specific legal rights, and you also may have other rights which vary from state to state. This warranty is not transferable. This warranty does not cover damage or defects relating to misuse, abuse, negligence, normal wear and tear, accident, acts of God, repairs or alterations not authorized in writing by Delta, or improper installation, storage or handling.

LIMITED WARRANTY

All parts and finishes of the Delta® shower unit are warranted to the original consumer purchaser to be free from defects in material and workmanship for the time periods listed below. Delta recommends using a professional plumber for all installation and repair. Delta will replace, FREE OF CHARGE, during the warranty period, any part or finish that proves defective in material and/or workmanship under normal installation, use and service for the time period listed below:

• Non-residential or commercial application - 3 years • Residential applications - 10 years

This warranty is extensive in that it covers replacement of all defective parts and even finish, but these are the only two things that are covered. LABOR CHARGES AND/OR DAMAGE INCURRED IN INSTALLATION, REPAIR, OR REPLACEMENT, AS WELL AS ANY OTHER KIND OF LOSS OR DAMAGE ARE EXCLUDED. Proof of purchase (original sales receipt) from the original consumer purchaser must be made available to Delta for all warranty claims. THIS IS THE EXCLUSIVE WARRANTY BY DELTA, WHICH DOES NOT MAKE ANY OTHER WARRANTY OF ANY KIND, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. Any damages to this product as a result of misuse, abuse, or neglect WILL VOID THE WARRANTY.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. It applies only to Delta® Shower Units installed in the United States of America, Canada and Mexico.

If you have any questions regarding technical support, installation or concerns regarding our warranty plan, please view our Warranty Frequently Asked Questions at www.deltafaucet.com/bathingsystems, email us at bathingsystems@deltafaucet.com, or call 1-877-430-5315.

DISCLAIMER: IMPLIED WARRANTIES, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE, ARE LIMITED TO THE DURATION OF THIS WARRANTY. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. TO THE EXTENT PERMITTED BY LAW, THIS WARRANTY DOES NOT COVER SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (SUCH AS LABOR EXPENSES) WHETHER ARISING OUT OF BREACH OF WARRANTY, BREACH OF CONTRACT, TORT, OR OTHERWISE. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation of exclusion may not apply to you. This warranty gives you specific legal rights, and you also may have other rights which vary from state to state. This warranty is not transferable. This warranty does not cover damage or defects relating to misuse, abuse, negligence, normal wear and tear, accident, acts of God, repairs or alterations not authorized in writing by Delta, or improper installation, storage or handling.

Manual de instalación



36" (91.4 cm)



48" (121.9 cm)



60" (152.4 cm)

Base de ducha

Anote el número de modelo indicado en el panel frontal de la caja.

Número de modelo: _____

Conserve estas instrucciones para usarlas en el futuro.

P/N 27793 09/13

PIEZAS INCLUIDAS



	A	B	C	D	E
Base de 36" (91,4 cm)	17" (43,4 cm)	35-7/8" (91,1 cm)	34-3/4" (88,2 cm)	4.5" (11,3 cm)	18" (45,7 cm)
Base de 48" (121,9 cm)	16" (40,9 cm)	47-7/8" (121,6 cm)	32-3/4" (83,1 cm)	4.5" (11,3 cm)	24" (61,0 cm)
Base de 60" (152,4 cm)	15" (38,3 cm)	59-7/8" (152,1 cm)	30-3/4" (78,1 cm)	4.5" (11,3 cm)	8-1/2" (21,4 cm)*

* Base de 60” (152,4 cm) disponible con conexión de las cañerías del lado derecho o izquierdo. Conexión de las cañerías del lado derecho.

REQUISITOS PARA UNA INSTALACIÓN CORRECTA

⚠ **PRECAUCIÓN: NO** utilice tornillos para placas de yeso para fijar las bridas a los montantes de la pared. Dañará el producto y dejará sin efecto la garantía.

- **Lea las instrucciones completas antes de comenzar la instalación.**
- **Estas instrucciones incluyen sugerencias que consideramos confiables para construcciones sin acabar e instalación de cañerías. Los códigos locales de construcción varían según el lugar y tienen prioridad sobre estas sugerencias. Si no se siente capaz de realizar estas tareas, tercerícelas o contrate un instalador profesional.**
- **Verifique que su modelo quepa en la ubicación deseada y que los accesorios de fontanería se encuentren donde sea necesario antes de iniciar la instalación.**
- **Las paredes y el contrapiso deben estar firmes, nivelados y en escuadra.**
- **Utilice una lona protectora para proteger la base de la ducha durante la instalación.**
- **No realice la instalación en áreas donde la temperatura pueda ser inferior a 32°F (0 °C).**
- **Deje que el producto alcance la temperatura ambiente durante 30 minutos antes de la instalación.**
- **Se recomienda que dos personas se encarguen de la instalación del producto.**

HERRAMIENTAS Y MATERIALES NECESARIOS

Gafas de seguridad


Navaja

Lápiz


Cinta métrica


Cuñas


Lona protectora


Escuadra


Nivel


Pistola para sellar


Adhesivo (2 tubos)


Sellador (2 tubos)

Taladro


Tornillos de 1-1/4" (3,1 cm) (de zinc o inoxidables, cilíndricos o de


Tornillos avellanados 2-1/2" (6,3 cm)

Sierra circular para taladro (con el tamaño necesario para accesorios de fontanería)

Sujetador de extensión para brocas (recomendado)

Broca Phillips N.º 2 (para uso con sujetador de extensión para brocas)


Broca de 3/16" (4,7 mm)

- Madera de 2” x 4” (5 cm x 10 cm) para montantes de pared adicionales
- Madera para sostener
- Trapos o almohadillas para proteger el producto durante la instalación de la madera para sostener

CONSEJO: Se recomienda instalar aislamiento.

CONEXIÓN DE CAÑERÍAS

36"



48"



60"





- Deben instalarse las cañerías antes de instalar los paneles.
- Los tamaños mínimos de los huecos del montante se muestran a continuación.

* Base de 60" (152,4 cm) disponible con conexión de las cañerías del lado derecho o izquierdo. Conexión de las cañerías del lado derecho.

****¡IMPORTANTE!** Si instala el juego de pared, consulte las instrucciones de instalación para el juego de pared y obtendrá los tamaños específicos y la ubicación de las maderas. Se necesitarán montantes adicionales y se deberán instalar en este punto.

- Para los trabajos de mampostería, el piso y las paredes deben enmarcarse de manera que alojen a las cañerías y a la instalación de esta unidad.

Instrucciones importante para realizar una instalación adecuada



⚠ PRECAUCIÓN: El mandril del taladro puede dañar la base. Haga los orificios desde la parte posterior de la base lateral.

SUGERENCIA: Si la superficie de instalación no está nivelada, use compuesto de nivelación o un lecho de mortero para realizar una instalación adecuada.

14. Símbolos y descripción

A APLIQUE ADHESIVO donde se indica.

S APLIQUE SELLADOR donde se indica.

⚠ PRECAUCIÓN: Una situación que, de no evitarse, podría producir daños materiales u otras condiciones no deseadas. Dañará el producto y dejará sin efecto la garantía.

¡IMPORTANT! Instrucciones que, de no seguirse, podrían producir daños materiales. Puede que el producto sufra daños que anulen la garantía.

15. Verifique el ajuste de la base



Coloque la base y verifique que esté derecha y en escuadra.

⚠ PRECAUCIÓN: Todo el soporte inferior debe estar en contacto con una superficie plana y nivelada.

SUGERENCIA: Si la superficie de instalación no está nivelada, use compuesto de nivelación o un lecho de mortero para realizar una instalación adecuada.

16. Prepare la base



- Trace el contorno de las ubicaciones del drenaje y de la base.

17. Instale el drenaje



- Instale el drenaje siguiendo las instrucciones del fabricante.

⚠ PRECAUCIÓN: La masilla de plomero degradará el material de la base. No use masilla de plomero para sellar entre el drenaje y la base. Utilice en cambio un sellador de látex/acrílico o una junta.

18. Haga orificios en la brida



- Haga orificios de 3/16” (4,7 mm) en todas las ubicaciones de los montantes en las bridas superiores.

⚠ PRECAUCIÓN: Haga orificios de separación de 3/16” (4,7 mm) únicamente en las bridas. No haga orificios de 3/16” (4,7 mm) directamente en los montantes. El mandril del taladro puede dañar los paneles. Utilice un sujetador de extensión para brocas para reducir el riesgo de que el mandril del taladro golpee la base.

19. Instale la tubería del drenaje



- Asegúrese de que la tubería de desechos esté correctamente ubicada para que quede alineada con el conjunto de desagüe (no se incluye).
- La apertura debería tener 5” (12,7 cm) de diámetro. El tubo de drenaje debe extenderse 1-3/4” (4,4 cm) sobre el contrapiso.

20. Optativo



- Si el contrapiso no está plano y nivelado, se recomienda colocar un lecho de mortero donde se ubicará la base.

21. Aplique adhesivo



A APLIQUE ADHESIVO en el piso y extiéndalo con el lado recortado de la llana, empezando dentro de la línea del lápiz.

22. Colocación final de la base



- Coloque la base sobre el piso cubierto de adhesivo y vuelva a comprobar la nivelación. Ajústela si es necesario.

23. Inserte cartón



- Inserte cartón u otro material en la base para proteger la superficie.

> ⚠ **PRECAUCIÓN:** No extraiga hasta que se hayan terminado todas las tareas en la habitación.

24. Fije la base



- Fije las bridas a los montantes de la pared utilizando tornillos de 1-1/4” (3,1 cm).

⚠ PRECAUCIÓN: Use tornillos cilíndricos o de cabeza redonda. No apriete los tornillos excesivamente o podría romper la base.

¡IMPORTANTE! Los espacios entre las bridas y los montantes deben ser inferiores a 1/8” (3 mm). Inserte cuñas para llenar todos los espacios.

25. Aplique sellador



⚠ PRECAUCIÓN: Después de instalar las paredes terminadas, recuerde aplicar sellador en todos los bordes exteriores.

Ⓢ APLIQUE SELLADOR donde se indica.

¡IMPORTANTE! Antes de utilizar el sellador, siga las instrucciones del fabricante acerca del tiempo de secado.

26. Continuar con el juego para pared



- Si instala nuestro juego para pared concordante, continúe con las instrucciones “Instalación del juego para pared”.

SERVICIO AL CLIENTE

Para consultas sobre el producto y la instalación, NO regrese a la tienda. Para obtener asistencia adicional, comuníquese con el servicio al cliente:

Ingrese a www.deltabathing.com, envíe un mensaje de correo electrónico a bathingsystems@deltafaucet.com o llame al ☎ 1-877-430-5315.

CUIDADO Y LIMPIEZA

Para la limpieza habitual, use SOLO detergentes suaves o agua tibia jabonosa. Use SOLO paños o esponjas no abrasivas. Siempre enjuague las superficies tras limpiarlas.

Antes de limpiar esta unidad con productos de limpieza, pruebe en un área pequeña que pase desapercibida.

⚠ **PRECAUCIÓN:** El fabricante no recomienda el uso de productos de limpieza que contengan alguno de los siguientes químicos. El uso de productos que contengan estas sustancias químicas puede generar grietas o decoloración y dejará sin validez la garantía.

- Nafta
- Acetato de amilo
- Solución de peróxido de hidrógeno (agua oxigenada de uso doméstico)
- Tolueno
- Acetato de etilo
- Lejía (común en destapacaños)
- Acetona

GARANTÍA LIMITADA

Se garantiza al comprador original que todas las piezas y los acabados de la ducha Delta® estarán libres de defectos de materiales y mano de obra por los periodos listados a continuación. Delta recomienda que un fontanero profesional realice todas las tareas de instalación y reparación. Delta reemplazará, GRATUITAMENTE, durante el periodo de la garantía, cualquier pieza o acabado que tenga defectos de mano de obra o de materiales cuando se instale, use y dé servicio de la manera correcta durante el periodo indicado a continuación:

• Aplicación no residencial o comercial: 3 años • Aplicaciones residenciales: 10 años

Esta garantía es extensa en el sentido de que cubre el reemplazo de todas las piezas y hasta el acabado defectuosos, pero estos son los únicos dos aspectos que se cubren. SE EXCLUYEN LOS CARGOS POR MANO DE OBRA O POR DAÑOS INCURRIDOS DURANTE LA INSTALACIÓN, REPARACIÓN O REEMPLAZO, ASÍ COMO CUALQUIER OTRO TIPO DE PÉRDIDAS O DAÑOS. En todas las reclamaciones de la garantía se debe presentar a Delta el comprobante de compra (recibo original de la compra) del comprador original. ESTA ES LA GARANTÍA EXCLUSIVA DE DELTA, QUE NO HACE NINGUNA OTRA GARANTÍA DE NINGUNA CLASE, INCLUIDA LA GARANTÍA IMPLÍCITA DE COMERCIALIZACIÓN.

Algunos estados no permiten la exclusión o la limitación de daños resultantes o incidentales, de manera que es posible que la limitación o exclusión antedicha no se aplique en su caso. Todos los daños a este producto que resulten del uso inadecuado, abuso o negligencia ANULARÁN LA GARANTÍA.

Esta garantía le brinda derechos legales específicos y es posible que usted tenga otros derechos que varían de un estado a otro. Aplica solo a las unidades de duchas Delta® instaladas en Estados Unidos, Canadá y México.

Si tiene alguna pregunta referente a la asistencia técnica o la instalación, o tiene inquietudes sobre nuestro plan de garantía, revise la sección de Preguntas frecuentes sobre la garantía en www.deltafaucet.com/bathingsystems, envíenos un mensaje electrónico a bathingsystems@deltafaucet.com, o llame al 1-877-430-5315.

DESCARGO DE RESPONSABILIDAD: LAS GARANTÍAS IMPLÍCITAS, INCLUIDAS AQUELLAS DE COMERCIALIZACIÓN E IDONEIDAD PARA UN PROPÓSITO PARTICULAR, SE LIMITAN A LA DURACIÓN DE ESTA GARANTÍA. Algunos estados no permiten la limitación en la duración de una garantía implícita, de manera que la limitación anterior podría no aplicarse a su caso. AL GRADO QUE LA LEY LO PERMITA, ESTA GARANTÍA NO CUBRE DAÑOS INCIDENTALES NI CONSECUENTES ESPECIALES (COMO GASTOS POR MANO DE OBRA) QUE SURJAN DEL INCUMPLIMIENTO DE LA GARANTÍA, INCUMPLIMIENTO DEL CONTRATO, PROCEDIMIENTO FRAUDULENTO O DE OTRO TIPO. Algunos estados no permiten la exclusión o la limitación de daños resultantes o incidentales, de manera que es posible que la limitación o exclusión antedicha no se aplique en su caso. Esta garantía le otorga derechos legales específicos, y es posible que tenga otros derechos que varían de un estado a otro. Esta garantía no es transferible. Esta garantía no cubre daños o defectos que se relacionen con uso inadecuado, abuso, negligencia, desgaste normal, accidentes, causas de fuerza mayor, reparaciones o alteraciones que no estén autorizadas por escrito por Delta, o la instalación, almacenamiento o manejo inapropiados del producto.